Reference Material - Data Summary Sheet

GP Batch: 1047-C-1

Product Type: Soil

Issue Date: 5 May 2026

Expiry Date: 30 June 2027

Test Name	n Labs	n Values	Mean	Uncertainty [1] of Mean	k	Methods
Acid P (mg/kg)	6	10	29.9	+/- 5.4	2.26	9G1, 9G2
Ammonium Nitrogen (mg/kg)	11	20	4.29	+/- 0.62	2.09	7C1, 7C2 *
Aqua Regia Aluminium (mg/kg)	7	10	26809	+/- 2800	2.26	17B1, 17B2, 17C1
Aqua Regia Arsenic (mg/kg)	7	10	3.24	+/- 0.39	2.26	17B1, 17B2, 17C1
Aqua Regia Cadmium (mg/kg)	5	8	0.0283	+/- 0.0062	2.36	17B1, 17B2, 17C1
Aqua Regia Calcium (mg/kg)	7	12	6678	+/- 286	2.20	17B1, 17B2, 17C1
Aqua Regia Chromium (mg/kg)	9	15	34.5	+/- 3.6	2.14	17B1, 17B2, 17C1
Aqua Regia Cobalt (mg/kg)	6	10	16.8	+/- 0.3	2.26	17B1, 17B2, 17C1
Aqua Regia Copper (mg/kg)	8	13	16.6	+/- 0.6	2.18	17B1, 17B2, 17C1
Aqua Regia Iron (mg/kg)	8	13	27184	+/- 2260	2.18	17B1, 17B2, 17C1
Aqua Regia Magnesium (mg/kg)	7	12	5246	+/- 358	2.20	17B1, 17B2, 17C1
Aqua Regia Manganese (mg/kg)	8	13	969	+/- 36	2.18	17B1, 17B2, 17C1
Aqua Regia Molybdenum (mg/kg)	6	11	0.216	+/- 0.089	2.23	17B1, 17B2, 17C1
Aqua Regia Potassium (mg/kg)	7	11	2744	+/- 359	2.23	17B1, 17B2, 17C1
Aqua Regia Sodium (mg/kg)	6	10	548	+/- 31	2.26	17B1, 17B2, 17C1
Aqua Regia Zinc (mg/kg)	7	12	42.0	+/- 3.7	2.20	17B1, 17B2, 17C1
CaCl2 Extractable B (mg/kg)	8	15	0.926	+/- 0.106	2.14	12C1, 12C2
Colwell P (mg/kg)	9	17	14.7	+/- 0.8	2.12	9B1, 9B2
Electrical Cond (dS/m)	18	32	0.158	+/- 0.006	2.04	3A1
Exch Aluminium (cmol+/kg)	4	8	0.0124	+/- 0.0063	2.36	15G1 *
Exch Calcium (cmol+/kg)	9	16	27.2	+/- 0.9	2.13	15A1 *

Global Proficiency Limited
10 Bisley Road, Enderley, Hamilton 3214, New Zealand
p +64 7 850 4483
e sales@global-proficiency.com
w www.global-proficiency.com

Exch Calcium (cmol+/kg)	9	16	26.9	+/- 0.6	2.13	15D3
Exch Magnesium (cmol+/kg)	9	16	12.1	+/- 0.3	2.13	15A1 *
Exch Magnesium (cmol+/kg)	9	17	11.8	+/- 0.3	2.12	15D3
Exch Potassium (cmol+/kg)	9	15	1.19	+/- 0.04	2.14	15A1 *
Exch Potassium (cmol+/kg)	9	15	1.12	+/- 0.03	2.14	15D3
Exch Sodium (cmol+/kg)	10	16	1.71	+/- 0.05	2.13	15A1 *
Exch Sodium (cmol+/kg)	8	14	1.56	+/- 0.03	2.16	15D3
Ext Manganese (mg/kg)	8	13	27.2	+/- 0.9	2.18	12A1
Ext Sulphur (mg/kg)	6	12	6.54	+/- 0.66	2.20	10D1
M3-Aluminium (mg/kg)	5	9	905	+/- 18	2.31	18F1
M3-Boron (mg/kg)	4	8	1.27	+/- 0.14	2.36	18F1
M3-Calcium (mg/kg)	5	9	5143	+/- 158	2.31	18F1
M3-Copper (mg/kg)	6	11	2.74	+/- 0.18	2.23	18F1
M3-Iron (mg/kg)	6	11	116	+/- 6	2.23	18F1
M3-Magnesium (mg/kg)	5	9	1418	+/- 47	2.31	18F1
M3-Manganese (mg/kg)	5	8	266	+/- 27	2.36	18F1
M3-Phosphorus (mg/kg)	6	10	15.2	+/- 1.5	2.26	18F1
M3-Potassium (mg/kg)	5	9	401	+/- 20	2.31	18F1
M3-Sodium (mg/kg)	5	8	362	+/- 17	2.36	18F1
M3-Sulphur (mg/kg)	4	8	9.78	+/- 1.55	2.36	18F1
Nitrate Nitrogen (mg/kg)	7	12	5.19	+/- 0.23	2.20	7B1, 7B2
Nitrate Nitrogen (mg/kg)	7	14	5.31	+/- 0.34	2.16	7C1, 7C2
Olsen P (mg/kg)	5	9	6.13	+/- 0.44	2.31	9C1, 9C2
Organic Carbon W&B (%)	9	16	0.652	+/- 0.054	2.13	6A1 *
pH Water (pH units)	19	34	8.31	+/- 0.06	2.03	4A1, 4A3

Total Carbon (%)	15	28	0.743	+/- 0.017	2.05	6B2
Total Nitrogen (%)	15	25	0.0618	+/- 0.0031	2.06	7A5
Total Organic Carbon (%)	17	28	0.701	+/- 0.024	2.05	6B1, 6B3 *
Water Ext Cl (mg/kg)	9	15	5.87	+/- 1.52	2.14	5A1, 5A2, 5A3

[1] *Uncertainty of Mean is an expanded standard error of the mean (SEM) with a level of confidence of 95%. The coverage factor (k) is the critical value of Student's t distribution with n - 1 degrees of freedom. This uncertainty may only represent the measurement reproducibility of the data used. It does not include all known associated uncertainties and does not suggest that all methods used are statistically equivalent.*

* *These methods should be reported on an oven dried basis (105°C) by using the formula given in method 2A1 of Rayment and Lyons 2011.*

Intended Use: For the verification of analytical methods used to determine attributes of Soil

Description: 150 g+ irradiated, packed in plastic jar

Homogeneity: This reference material has been assessed as homogeneous.

Stability: An expiry period consistent with the shelf life of the unopened product and/or estimated from stability studies has been applied.

Storage: Keep samples dry and at a stable temperature (e.g. in air conditioned storage). Reseal containers immediately after each use. Do not store in sunlight.

Instructions for Use: Sample test portion size must be as stated in the method used in your laboratory; modification could invalidate the Reference values. Due to possible moisture reabsorption, re-dry the sample at 40°C to constant weight prior to analysis

Reference Values: The Mean is the simple mean excluding outliers; *n labs* is the number of laboratories who contributed results, and *n values* is the number of results used to calculate the mean. The uncertainty of the mean is the range within which the true mean of the population can be expected to lie with 95% confidence. This value is derived in accordance with the procedures described in ISO 33405:2024 "Reference materials - Approaches for characterization and assessment of homogeneity and stability".

Quality Statement: The values shown have been generated from data submitted in an inter-laboratory comparison programme (ILCP). The ILCP and reference material production are accredited to ISO/IEC 17043:2023 and ISO 17034:2016 respectively. Generation of this reference material also includes the requirements of ISO 33401 and 33405, which relate to production, characterisation and final product presentation.

Authorised by: Emily Hanna (Global P) - Key Technical Person

